



### LGSS4000 Chipping Spreader

The LGSS4000 self-propelled chip spreader is widely applied to continuously spread aggregate in the construction works of bituminous pavement construction and maintain. The roller speed and spreading speed can be controlled proportionally, as well as the belt speed and spreading speed. Auger speed and roller speed is synchronized, in favor of conveying material and preventing unmixing. Self-locking traction hook can realize the easy connection and disconnection between spreader and dumper truck during continuous spreading. Two independent braking system to facilitate the reasonable safety of traveling.

#### Specification:

Engine	
Model	WD615.50
Type	Water cooled turbocharged
Rated power	206kw
Rated speed	2200rpm
Main Technical Specification	
Spreading width	250-4000mm
Spreading speed	2.5-3.6km/h
Max.running speed	23
Spreading capacity	2-30m <sup>3</sup> /km <sup>2</sup>
Aggregate size	3-40mm
Dimensions	
Overall length	7270mm
Overall width	2855mm
Overall height	2700mm

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

E-mail: [info@shlongji.com](mailto:info@shlongji.com)

Tel: +86-21-541-71571

Fax: +86-21-541-71572