

LG5253GJB Concrete Truck Mixer

Engine			
Model	Cummins L37	75 20	
Туре	Water cooled	,turbocharged	
Rated power	275kw		
Rated speed	2200rpm		
Main Technical Specification			
Chassis model		DFL5310GJBAX	
N.V.W		14870kg	
Payloading capacity		31000kg	
G.V.W		46000kg	
Axle loading capacity(F/R)		2×10000/2×16000kg	
Max.traveling speed		90km	
Grade ability		48%	
Approach angle		16°	
Departure angle		25°	
Ground clearance		298mm	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai

City, China

Post Code: 201100 E-mail: mailto:info@shlongji.com

Tel: +86-21-541-71571 Fax: +86-21-541-71572

Dimensions		
Overall size	10520×2500×3994mm	
Wheel base	1850/3400/1350mm	
Tread(F/R)	2027/2027/1820/1820mm	
Transmission System		
9JS150T-B .9 forward & 1 reverse		
Ratio		
Forward	12.65,8.38,6.22,4.57,3.40,2.46,1.83,1.34,1.00	
Reverse	12.66	
Mixer Drum		
Effective capacity	12m3	
Leaning angle	15°	
rotation speed	0-12rpm	
Feeding speed	≥3m3/min	
Discharging speed	≥2m3/min	
Landslide speed	70-260mm	
Surplus rate	≤1%	
Water tank	400L	
Axle And Type		
Front axle	Dongfeng	
Rear axle	Dongfeng	
Ratio	5.143	
Tyre size	12.00-20	
Steering System		
ZF8098,Hydraulic steering with power		
assistance		
Ratio	22.2-26.2	
lutch Amd Brakes		
Single—plate dry coil-spring clutch, hydra	aulically operated with air assistance	
Service brake	Dual circuit compressed air brake	
Parking brake	Spring energy operating on rear wheels	
Auxiliary brake	Engine exhaust brake	
Cab		
D310, four point full-floating damper, hydra	aulically damped adjustable driver's seat and rigid adjustable co	
driver's seat, heating and ventilation system ,no sleeper		

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai

City, China

Post Code: 201100 E-mail: mailto:info@shlongji.com

Tel: +86-21-541-71571 Fax: +86-21-541-71572