

Crawler Excavator LGE230LC

Engine	
Model	Cummins 6BTA5.9-C173(UK)
Туре	Direct injection, water cooled
Rated power	126kw
Rated speed	2200rpm
Main Technical Specification	·
Operating weight	23000kg
Standard bucket capacity	1.0m3
Slewing speed	13rpm
Stick digging force	109KN
Bucket digging force	135.9KN
Hydraulic System	·
Main pump	KAWASAKI
Main valve	TOSHIBA/Parker
Motor	TOSHIBA/Parker
Hydraulic flow rate	2×238L/min
Hydraulic pressure	30Mpa
Traveling System	
Traveling speed	3-5Km/h
Grade ability	65%
Ground pressure	0.045Mpa
Dimensions	
Overall length	9845mm
Overall width	3000mm
Overall height of boom	3300mm
Overall height of cab	2755mm
Engine cover height	2300mm
Counterweight clearance	1060mm
Ground clearance	465mm

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Upperstructure width	2710mm
Rear-end length/Slewing radius	2940mm
Overall track length	4510mm
Track length of ground	3720mm
Track gauge	2400mm
Track width	600mm
Boom slewing angle(L/R)	0°
Operating Scope	
Stick length	3000mm
A:Max cutting height	9650mm
B:Max dumping height	7150mm
C:Max digging depth	7050mm
D:Max reach	10400mm