

LGDT3311F Dump Truck

Dimensions		
Overall size(L× W× H)	10490mm×2500mm×3450mm	
Cargo body size(L × W ×H)	7800mmx2260mmx1040mm	
Wheelbase	3800mm 1350mm	
Wheel track(Front/Rear)	2027mm/1820mm	
Minimum ground clearance	300mm	
Weight		
N.V.W	12300kg	
Pay loading capacity	30000kg	
Gross vehicle weight	43000kg	
Axle loading capacity(Front/Rear)	2×9000/2x15000kg	
Performance		
Maximum driving speed	80km/h	

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, ShanghaiCity, ChinaPost Code: 201100E-mail: mailto:info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Minimum turning circle	18m	
Maximum grade ability	35%	
Approach angle	30°	
Departure angle	24°	
Fuel consumption	35L	
Engine	•	
Model	Cummins L340-30	
T. m. c	6 cylinder in line, turbo, air-air intercooled, diesel	
Туре	engine	
Rated power	250kW(340HP)	
Maximum torque at 1200~1400rpm	1180(N.m)	
Displacement	8500ML	
Compression ratio	18:01	
Driver's Cab	•	
Dong FengD310-S1 (single sleeper, standard type)		
Transmission		
Туре	RT-11509C forward 9, reverse 1	
	1st: 12.42; 2nd:8.62; 3rd:6.08; 4th:4.53; 5th:3.36;	
Ratio	6th:2.47;; 7th:1.81; 8th:1.35; 9th: 1	
	Reverse: 12.99	
Steering		
ZF steering		
Ratio		
Front axle		
Dong Feng- Hande,		
Rear axle		
Dong Feng-Hande reinforced, hub reducing axle		
Ratio	5.92	
Clutch	-	
Ф430mm, diaphragm spring clutch		
Brakes		
Service brake: dual circuit compressed air brake		
Parking brake: spring energy operating on rear who	eels	
Auxiliary brake: engine exhaust brake		
Wheels rim& Tyres		
Rims	8.50R20	
Tyres	12.00R20	
Electric System	-	
Operating voltage	24V	

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, ShanghaiCity, ChinaPost Code: 201100E-mail: mailto:info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Alternator	1500W
Batteries	24V/165Ah
Fuel tank	
Capacity	350L