

SWC212H Tandem Vibratory Roller(Hydraulic Transmission)

Hydraulic double drum vibratory road roller SWC212H adopts dual frequency and amplitudes vibration system with imported piston pump and motors, center articulated steering with crabwalk unit for flexible maneuverability, integrated multi-disc wetbrake with oil-cutoff braking for reliable safety, electric power sprinkler system with large capacity reinforced polyethylene water tank, which ensure you to achieve high working efficiency.

Engine	
Model	Cummins 6BT5.9
Туре	Vertical, water cooled, direct injection
Rated power	110KW
Rated speed	2300rpm
Rated fuel consumption	215g/kw⋅h
Main Technical Specification	
Operating weight	12000kg
Туре	Hydraulic vibration
Frequency	40/46Hz
Amplitude	0.4/0.8mm
Static linear load	286/286N/cm
Vertical oscillation	8°
Drum shell thickness	20mm
Centrifugal force(high ampl.)	160KN×2
Centrifugal force(low ampl.)	90KN×2
Transmission System	
Туре	Hydraulic drive
Grade ability	40%
Traveling speed(km/h)	
Forward/Reverse	0-12
Traveling pump	SAUER/REXROTH piston pump
Traveling motor	SAUER/REXROTH piston motor
Axle	
Drive type	Dual wheel drive
Front axle load	6000kg

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Rear axle load	6000kg
Steering System	·
Туре	Articulated frame, hydraulic steering
Steering cylinder	Two cylinders
Steering pump	Gear pump
Working pressure	13MPa
Steering angle	±35°
Min. steering radius	5605mm
Braking System	
Service brake	Oil cut off brake
Parking brake	Button operated
Dimensions	· · · ·
Overall length	5062mm
Overall width	2250mm
Overall height	3000mm
Drum width	2100mm
Wheel base	3717mm
Drum Dia.	1350mm
Ground clearance	324mm
Service Capacities	· · · · ·
Hydrauclic tank	65L
Vibrating bearing	20L
Coolant liquid	34L
Reducer	2.6L
Fuel tank	154L
Engine crank case	16L