

SWC214H Tandem Vibratory Roller(Hydraulic Transmission)

SWC214H hydraulic double drum vibratory road roller adopts dual frequency and amplitudes vibration system with imported piston pump and motors, center articulated steering with crabwalk unit for flexible maneuverability, integrated multi-disc wet brake with oil-cutoff braking for reliable safety, electric power sprinkler system with large capacity reinforced polyethylene water tank, which ensure you to achieve high working efficiency.

Cummins 6BT5.9
Vertical,water cooled,direct injection
110KW
2300rpm
215g/kw·h
14000kg
Hydraulic vibration
40/50Hz
0.4/0.8mm
333/333N/cm
8°
20mm
160KN×2
90KN×2
Hydraulic drive
40%
0-12
SAUER/REXROTH piston pump
SAUER/REXROTH piston motor

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Drive type	Dual wheel drive
Front axle load	7000kg
Rear axle load	7000kg
Steering System	
Туре	Articulated frame, hydraulic steering
Steering cylinder	Two cylinders
Steering pump	Gear pump
Working pressure	13MPa
Steering angle	±35°
Min. steering radius	5605mm
Braking System	
Service brake	Oil cut off brake
Parking brake	Button operated
Dimensions	
Overall length	5062mm
Overall width	2250mm
Overall height	3000mm
Drum width	2100mm
Wheel base	3717mm
Drum Dia.	1350mm
Ground clearance	324mm
Service Capacities	
Hydrauclic tank	65L
Vibrating bearing	20L
Coolant liquid	34L
Reducer	2.6L
Fuel tank	154L
Engine crank case	16L