

LGS5221GLQ Intelligentized Asphalt Distributor

LGS5221GLQ intelligentized asphalt distributor is widely used in high-classified highway construction, which is suitable for asphalt pavement construction for improving construction efficiency. It is composed of truck chassis, asphalt tank, heat conducting oil, asphalt pumping and spraying system, hydraulic system, electric auto-controlling system, cleaning system, etc. Engineered by computer to deliver accurate, uniform, economical and convenient applications, and total vehicle performance achieve the international advanced standard.

| Engine | |
|------------------------------|--|
| Model | WD615.62/87 |
| Туре | Water-cooled, turbocharged |
| Rated power | 196/213KW |
| Rated speed | 2200rpm |
| Main Technical Specification | |
| Chassis model | ZZ1167M4611W |
| Spray width | 200-6000mm |
| Spray volume | $0.2-3.0 \text{kg/m}^2$ |
| Asphalt tank volume | 8500L |
| Asphalt heater | Imported diesel oil burner |
| Spray media | Hot(modified)asphalt, diluted asphalt, emulsified asphalt, etc |
| Spray precision | ±1.5° |
| N.V.W | 8010kg |
| Payloading capacity | 9000kg |
| G.V.W | 17500kg |
| Axle loading capacity(F/R) | 8000/9500kg |
| Max. traveling speed | 90km/h |
| Approach angle | 23° |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100 E-mail: <u>info@shlongji.com</u> Tel: +86-21-541-71571 Fax: +86-21-541-71572

| Departure angle | 15° |
|-------------------------------------|---|
| Automatic Control System | • |
| Туре | Two set control systems(In-cab and rear |
| | operation panel) |
| Spray value control | Adjusted automatically according to working |
| | speed |
| Nozzle control | Making any combination by industrial |
| | computer independently |
| Heat conducting oil control | By microcomputer automatically |
| Transmission System | |
| F9 mechanical type | |
| Ratio | |
| Forward | 12.42,8.26,6.08,4.53,3.36,2.47,1.81,1.35,1.00 |
| Reverse | 12.99 |
| Axle And Type | |
| Front axle | HOWO |
| Rear axle | HOWO |
| Ratio | 4.8 |
| Tyre size | 12.00-20 |
| Steering System | |
| Hydraulic steering | |
| Clutch And Brake | |
| Single-plate dry coil-spring clutch | |
| Service brake | Air brake |
| Parking brake | Mechanical |
| Dimensions | |
| Overall length | 9030mm |
| Overall width | 2496mm |
| Overall height | 3490mm |
| Wheel base | 4600mm |
| Tread(F/R) | 2022/1830mm |
| | |

Tel: +86-21-541-71571 Fax: +86-21-541-71572