

LGD220Y Crawler Bulldozer(Dozer)

Engine	
Model	Cummins NT-855
Type	Vertical, four-stroke
Rated power	162kw
Rated speed	1800rpm
Implement Hydraulic System	
Hydraulic flow rate	257L/min
Hydraulic pressure	13.7Mpa
Pump type	Double gear pump
Control valve	Hydraulic operated pilot control
Under Carriage System	
Sprocket	Segmented
Number of track rollers(each side)	6(4 single, 2double)
Number of carrier rollers(each side)	2
Number of front idler(each side)	1
Track type	Single grouser
Track tension	Hydraulic
Track pitch	216mm
Track width	560mm
Number of track shoes (each	38

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China Post Code: 201100 E-mail: info@shlongji.com
Tel: +86-21-541-71571 Fax: +86-21-541-71572

website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck

Track length of ground 2730mm Ground clearance 405mm Main Technical Specifications Operation weight(without ripper) 25500kg Ground pressure (without ripper) 0.078Mpa Grade ability 58% Overall dimensions(LxWxH,with single shank ripper) Max.tractive force 200KN Working Equipment Blade type Straight Width 3725mm
Ground clearance 405mm Main Technical Specifications Operation weight(without ripper) 25500kg Ground pressure (without ripper) 0.078Mpa Grade ability 58% Overall dimensions(LxWxH,with single shank ripper) 6850x3725x3575mm Max.tractive force 200KN Working Equipment Blade type Straight Width 3725mm
Main Technical SpecificationsOperation weight(without ripper)25500kgGround pressure (without ripper)0.078MpaGrade ability58%Overall dimensions(LxWxH,with single shank ripper)6850x3725x3575mmMax.tractive force200KNWorking EquipmentStraightBlade typeStraightWidth3725mm
Operation weight(without ripper)25500kgGround pressure (without ripper)0.078MpaGrade ability58%Overall dimensions(L×W×H,with single shank ripper)6850×3725×3575mmMax.tractive force200KNWorking EquipmentStraightBlade typeStraightWidth3725mm
Ground pressure (without ripper) 0.078Mpa Grade ability 58% Overall dimensions(L×W×H,with single shank ripper) 6850×3725×3575mm Max.tractive force 200KN Working Equipment Blade type Straight Width 3725mm
Grade ability 58% Overall dimensions(L×W×H,with single shank ripper) 6850×3725×3575mm Max.tractive force 200KN Working Equipment Blade type Straight Width 3725mm
Overall dimensions(L×W×H,with single shank ripper) Max.tractive force 200KN Working Equipment Blade type Straight Width 3725mm
single shank ripper) Max.tractive force Working Equipment Blade type Straight Width 3725mm
Max.tractive force 200KN Working Equipment Blade type Straight Width 3725mm
Working Equipment Blade type Straight Width 3725mm
Blade type Straight Width 3725mm
Width 3725mm
Height 1315mm
Max digging depth 540mm
Max.lift above ground 1210mm
Tilting angle 11°
Blade Capacity 5.45m3
Transmission System
Torque converter 3-elements, single stage.single phase
Power shift ,forced lubricated planetary
Gear box gear
Bevel gear Helical bevel gear splash lubricated
Spur gear, double reduction splash
Final drive lubricated
Gear shifts(Forward/Reverse) F3/R3
Traveling speed (km/h)
Forward/Reverse I 3.6/4.3
Forward/Reverse II 6.5/7.7
Forward/ReverseIII 11.2/13.2
Steering Clutch And Brake
Wet multiple disc spring loaded
Steering clutch hydraulically released
Wet hand brake operated with hydraulic
Steering brake booster valve inner linkage
Service Capacities
Fuel tank 450L
Water tank 79L
Implement oil tank 110L

website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck