

LGD220YS Crawler Bulldozer(Dozer)

Engine	
Model	Cummins NT-855
Туре	Vertical,four-stroke turbocharged
Rated power	162kw
Rated speed	1800rpm
Implement Hydraulic System	
Hydraulic flow rate	257L/min
Hydraulic pressure	13.7Mpa
Pump type	Double gear pump
Control valve	Hydraulic operated pilot control
Under Carriage System	
Sprocket	Segmented
Number of track rollers(each side)	8(5 single, 3double)
Number of carrier rollers(each side)	2
Number of front idler(each side)	1
Track type	Single grouser
Track tension	Hydraulic
Track pitch	216mm
Track width	945mm
Number of track shoes (each side)	45
Track length of ground	3490mm
Ground clearance	450mm
Main Technical Specifications	
Operation weight	26000kg

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572 website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck

Ground pressure	0.038Mpa
Grade ability	58%
Overall dimensions(L×W×H)	6061×4365×3611mm
Max.tractive force	200KN
Working Equipment	
Blade type	Straight
Width	4365mm
Height	1260mm
Max digging depth	500mm
Max.lift above ground	1350mm
Tilting angle	11°
Blade Capacity	5.45m3
Transmission System	
Torque converter	3-elements, single stage.single phase
Gear box	Power shift ,forced lubricated planetary gear
Bevel gear	Helical bevel gear splash lubricated
Final drive	Spur gear, double reduction splash lubricated
Gear shifts(Forward/Reverse)	F3/R3
Traveling speed (km/h)	
Forward/Reverse I	3.6/4.3
Forward/Reverse II	6.5/7.7
Forward/ReverseIII	11.2/13.2
Steering Clutch And Brake	
Steering clutch	Wet, multiple disc, spring loaded hydraulically released
Steering brake	Wet, band brake operated with hydraulic booster valve inner linkage
Service Capacities	
Fuel tank	450L
Water tank	80L
Implement oil tank	110L