

LGD320YCrawler Bulldozer(Dozer)

LGD5201 Clawler Dundozer (Dozer)	
Cummins NTA855	
Vertical, four-stroke	
239kw	
2000rpm	
335L/min	
13.7Mpa	
Double gear pump	
Hydraulic operated pilot control	
Segmented	
7(5 single, 2double)	
2	
1	
Single grouser	
Hydraulic	
228.6mm	
560mm	
41	
3150mm	
500mm	

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572 website: www.shlongji.com Wheel Loader, Road Roller, Dump Truck

Main Technical Specifications	
Operation weight(without ripper)	35900kg
Ground pressure (without ripper)	0.094Mpa
Grade ability	58%
Overall dimensions(L×W×H,with single shank	
ripper)	8500×4130×3640mm
Max.tractive force	281KN
Working Equipment	
Blade type	Semi-U
Width	4130mm
Height	1590mm
Max digging depth	560mm
Max.lift above ground	1560mm
Tilting angle	14°
Blade Capacity	9.96m3
Transmission System	
Torque converter	3-elements, single stage.single phase
Gear box	Hydraulic actuated,forced lubricated planetary gear
Bevel gear	Helical bevel gear splash lubricated
Final drive	Spur gear, double reduction splash lubricated
Gear shifts(Forward/Reverse)	F3/R3
Traveling speed (km/h)	
Forward/Reverse I	3.6/4.3
Forward/Reverse II	6.6/7.8
Forward/ReverseIII	11.5/13.5
Steering Clutch And Brake	
	Wet, multiple disc, spring loaded hydraulically
Steering clutch	released
Steering brake	Wet,band brake,operated with hydraulic booster
Service Capacities	
Fuel tank	600L
Water tank	121L
Implement oil tank	164L