

LGD7Crawler Bulldozer(Dozer)



Large Engine Hood for Easy Maintenance

LGD7<u>Crawler Bulldozer(</u>Dozer)

Engine	
Model	Cummins NT855
Туре	Vertical,water cooled

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572website: www.shlongji.comWheel Loader, Road Roller, Dump Truck

Rated power	169kw
Rated speed	2100rpm
Implement Hydraulic System	
Hydraulic flow rate	194L/min
Hydraulic pressure	18.6Mpa
Pump type	High pressure gear pump
Control valve	Hydraulic operated pilot control
Under Carriage System	
Sprocket	Elevated
Number of track rollers(each side)	7(4 single, 3double)
Number of carrier rollers(each side)	2
Number of front idler(each side)	1
Track type	Single grouser
Track tension	Hydraulic
Track pitch	404mm
Track width	560mm
Number of track shoes (each side)	40
Track length of ground	2890mm
Ground clearance	404mm
Main Technical Specifications	
Operation weight(without ripper)	23800kg
Ground pressure (without ripper)	0.0719Mpa
Grade ability	58%
Overall dimensions(LxWxH,with single	7004 0500 0400
shank ripper)	7604×3500×3402mm
Max.tractive force	280KN
Working Equipment	
Blade type	Straight
Width	3500mm
Height	1550mm
Max digging depth	500mm
Max.lift above ground	1170mm
Tilting angle	9°
Blade Capacity	8.4m3
Transmission System	
Torque converter	Power separating hydraulic mechanical type
Transmission assembly	Integrated bevel gear, multiple stage gear box, speed
	changing control valve
Final drive	Two stage planetary reduction gear mechanism
Gear shifts(Forward/Reverse)	F3/R3
Traveling speed (km/h)	
Forward/Reverse I	3.9/4.8
Forward/Reverse II	6.5/8.2
Forward/ReverseIII	10.9/13.2

 Shanghai Longji Construction Machinery Co., Ltd.

 Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

 Post Code: 201100
 E-mail: info@shlongji.com

 Tel: +86-21-541-71571
 Fax: +86-21-541-71572

 website: www.shlongji.com
 Wheel Loader, Road Roller, Dump Truck

Steering Clutch And Brake	
Steering clutch	Oil-type,free-adjustment,multiple disc,pressed hydraulically
Steering brake	Pressed by spring separated hydraulically,constant meshed
	type
Service Capacities	
Fuel tank	450L
Water tank	118L
Implement oil tank	100L