

SWP1826H Pneumatic Tire Roller(Hydraulic Transmission)

SWP1826H pneumatic tire roller adopts Cummins engine, hydrostatic drive with stepless speed change, five tyres in front and six in rear, which is super quality compaction equipments for high-class highway, airport, municipal road and industrial ground, especially for final compaction of asphalt surface on high-class highway.

on night blabb highway.	
Engine	
Model	Cummins 6BTA5.9
Туре	Vertical,water cooled,direct injection
Rated power	125KW
Rated speed	2000rpm
Rated fuel consumption	200g/kw·h
Transmission System	
Туре	Mechanical or hydraulic drive
Grade ability	20%
Traveling speed(km/h)	
Forward/Reverse	0-14
Axle And Tyre	
Type of main reducer	Spiral bevel gear
Gear ratio	1:6.17
Final Reducer	Chain driven
Chain gear ratio	1:2.17
Single tyre load(F/R)	1560kg
Tyre number(F R)	5 6
Tyre size	11.00-20.16
Main Technical Specification	
Max.operating weight	26000 kg
Min.operating weight	18000 kg
Average ground pressure	0.2-0.42Mpa
Tyre pressure	0.2-0.8Mpa
Compacting width	2790mm
Vertical oscillation	±100mm
Steering System	

Shanghai Longji Construction Machinery Co., Ltd.Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, ChinaPost Code: 201100E-mail: info@shlongji.comTel: +86-21-541-71571Fax: +86-21-541-71572

Туре	Hydraulic steering
Working pressure	13MPa
Steering cylinder	Ф90×50×260mm
Min. steering radius	8000mm(outer side)
Braking System	
Service brake	Hydraulic brake
Parking brake	Oil cut off brake
Service Capacities	
Hydrauclic tank	67L
Gear box	10L
Fuel tank	220L
Engine crank case	16L
Dimensions	
Overall length	4878mm
Overall width	2800mm
Overall height	3103mm
Wheel base	3800mm
Ground clearance	300mm