

## Small Crawler Bulldozer LGD100S

Engine		
Model	LR6105T13A	
Туре	Turbocharged, water cooled, direct	
	injection	
Rated power	73.5kw	
Rated speed	2300rpm	
Implement Hydraulic System		
Hydraulic pressure	16Mpa	
Pump type	Gear pump	
Hydraulic flow rate	115L/min	
Valve position	4 position: raise, hold, lower, float	
3 position: raise, hold, lower		
Under Carriage System		
Sprocket	Segmented	
Number of track rollers(each side)	6	
Number of carrier rollers(each side)	1	
Number of front idler(each side)	1	
Track type	Single grouser	
Track pitch	171mm	
Track width	720mm	
Number of track shoes (each side)	39	
Track length of ground	2160mm	
Ground clearance	368mm	
Main Technical Specifications		
Operation weight	11360kg	
Ground pressure	0.036Mpa	
Grade ability	58%	
Overall dimensions(LxWxH)	4250mm×3240mm×3020mm	

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China Post Code: 201100 E-mail: info@shlongji.com
Tel: +86-21-541-71571 Fax: +86-21-541-71572

website:www.shlongji.com Wheel Loader, Road Roller, Dump Truck

Max.tractive force		81KN
Working Equipment		
Blade type		Straight
Width		2935mm
Height		960mm
Max digging depth		350mm
Max.lift above ground		830mm
Transmission System		
Gear box		Mechanical
Bevel gear		One pair spiral bevel gear
Final drive		One pair columnar gear, floating sealing
Gear shifts(Forward/Reverse)		F4/R2
Traveling speed (km/h)		
Forward I-IV		2.6-10.4
Reverse I-II		3.7-6.7
Steering Clutch And Brake		
Steering clutch	Dry multi-plate, floating control	
Steering brake	Mechanical pedal control	
Service Capacities		
Fuel tank	250L	
Water tank	22L	
Gear box	30L	