



DFL4180A2 Truck Tractor

| | |
|------------------------------|----------------------------|
| Engine | |
| Model | Cummins L340 30 |
| Type | Water cooled, turbocharged |
| Rated power | 253kw |
| Rated speed | 2200rpm |
| Main Technical Specification | |
| N.V.W | 7800kg |
| Permitted towing mass | 40000kg |
| Max. Traveling speed | 98km/h |
| The fifth wheel | 90# |
| Approach angle | 18° |
| Departure angle | 32° |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572

| | |
|---|---|
| Front overhang | 1500 |
| Rear overhang | 1080 |
| Dimensions | |
| Overall size | 5980×2500×3600mm |
| Wheel base | 3400mm |
| Tread | 2027/1860mm |
| Transmission System | |
| RT11509C synchromesh.9 forward & 1 reverse | |
| Ratio | |
| ---Forward | 12.42,8.26,6.08,4.53,3.36,2.47,1.81,1.35,1.00 |
| ---Reverse | 12.99 |
| Axle And Type | |
| Front axle | 5 ton |
| Rear axle | 13 ton |
| Ratio | 4.11 |
| Tyre size | 11.00R20 |
| Clutch And Brakes | |
| Single—plate dry coil-spring clutch, hydraulically operated with air assistance | |
| Service brake | Dual circuit compressed air brake |
| Parking brake | Spring energy operating on rear wheels |
| Auxiliary brake | Engine exhaust brake |
| Electric System | |
| Negative grounded | |
| System voltage | 24V |
| Batteries | 24V/165Ah |
| Cab | |
| Flat head, high roof with sleeper type, new inside decoration | |

Shanghai Longji Construction Machinery Co., Ltd.

Add: Room 1311, Building C, Lane 58, No.1 East Xinjian Road, Minhang District, Shanghai City, China

Post Code: 201100

Tel: +86-21-541-71571

E-mail: <mailto:info@shlongji.com>

Fax: +86-21-541-71572